

RULE BOOK DISCLAIMER

The rules and/or regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules. **NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM PUBLICATIONS OF OR COMPLIANCE WITH THESE RULES AND OR REGULATIONS.** They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator, or official.

The race director shall be empowered to permit reasonable and appropriate deviation from any of the specifications herein or impose any further restrictions that in his/her opinion does not alter the minimum acceptable requirements. **NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM SUCH ALTERATION OF SPECIFICATIONS.** Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is final.

The Management of Hummingbird Speedway

2021 HUMMINGBIRD SPEEDWAY 4-CYLINDER RULES

- See General Rules Tab for safety information pertaining to Roll Cages, and any other information regarding procedures and policies.

We follow SCDRA rules with a few exceptions and additions which are highlighted.

Basics:

- Must be a stock 4 cylinder car
- No turbo or rotary engines allowed
- Stock-type fuel injection or stock manufactured carburetor only (Motorcraft, etc...).
ONE 0.800" maximum throttle body spacer may be used. No Holley, Weber or other racing carburetors allowed. Carburetor must be stock for engine.
- Motor must be stock appearing and in stock location
- Motor must match car (ex. Honda must have Honda engine)
- Any air or oil filters (K&N, etc.)
- Intake must be a stock intake. No Skunk 2, etc.
- No cold air intakes for fuel injections – must be stock type breather system. A flexible rubber or plastic hose may be used in place of the stock air box tube. No smooth metal or smooth plastic tubing allowed. A cone type filter is allowed and may be connected directly to throttle body or the allowed tubes.
- Aftermarket radiators okay – radiators can be braced for support
- Aftermarket (racing) headers are allowed. ***No claim Rule
- Computer may be chipped and/or tuned. A standalone ECU and aftermarket harness are allowed. Ignition coil must remain OEM

Weight Rules:

- All cars must weigh 2,200 pounds with car and driver after the race
Exceptions: 50 lb. weight break for HANS or like device
50 lb. weight break for containment seat

Body / Wheel / Tire Rules:

- Any front wheel drive car
- No all-wheel drive cars or all wheel steer cars
- Must have stock rear and front suspensions as from factory, Slotting of factory mounting holes allowed.
- No racing springs (lowering) or shocks allowed. Springs may be heated, clamped or use spring rubbers. Springs must be within 2' of factory installed height
- Rear control arms should be stock but may be braced / strengthened / repaired. No aftermarket.
- Stock type aftermarket suspension bushings are allowed
- Stock production cars only
- Mirrors are NOT allowed
- Must have a quality welded MINIMUM 4 point roll cage inside the car with a minimum of 0.95" thickness tubing –
Hummingbird Speedway Tech has final say in safety of the cage
- Minimum 3 driver door bars / 2 side door bars – 6 or more point cages okay
- No push bars past firewall. Roll cage may extend forward behind bumpers. Bumpers must be covered in some way with no exposed sharp corners

- Aftermarket racing wheels allowed – 7 inch maximum. NO BEAD LOCKS
- Street legal DOT tires required. No drag radials, mud grip lug tires, racing tires or racing recapped tires allowed. Directional tires are allowed.
- Tires can be mixed and matched for stagger
- Aftermarket nose pieces allowed.
- 6 inch metal support to extend out behind nosepiece or to hold grill in place allowed
- No push bars to extend outside of bumpers or beyond nose piece.
- Some sheet metal will be allowed for repairs. Cars should remain as close to stock appearing as possible. Adding sheet metal to bodies may result in a weight penalty being assessed.
- Gutting of body is allowed.

Safety:

- Window nets are MANDATORY. Sprint-Style window nets will NOT be permitted.
- RACING (not motorcycle) helmet, SA 2005 or newer is required.
- Minimum single-layer fire suit required (SA 3.2A specification recommended).
- Fire proof gloves strongly recommended (SFI 3.3 specification recommended).
- A 4 or 5 point harness, properly mounted per manufacturers' specifications, is required. Must have been manufactured in the last 5 years. Any worn, abraded or torn belts shall be replaced.
- A minimum 5 lb. fire extinguisher is recommended and should be securely mounted within drivers reach.
- Only racing-type seats, properly mounted per manufacturers' specifications, are allowed. A full containment seat is strongly recommended. Cars equipped with full containment seats will receive a 50 lbs. weight break.
- A head and neck restraint system (SFI 16.1 compliant) is strongly recommended. Drivers using a head and neck restraint will receive a 50 lbs. weight reduction.
- A firewall must be in place between driver compartment and fuel cells, fuel lines or tanks.

Miscellaneous Rules:

- Hummingbird Speedway Tech has final ruling on all questions of legality. A pre-race inspection will be made to ensure SAFETY only.
- Questions of legality can and will be answered during the pre-race inspection if asked by entrant. No guarantee of legality shall be expressed or implied during pre-race inspection. Legality will be determined in POST-race inspection.
- Competitors must present cars for inspection prior to participating in any racing event. - No radios allowed
- RACEceivers or a like device is mandatory at all times on track.
- Red MyLaps Transponders are also required. Please see mounting instructions section for more info.